



### Product Highlights


- Linear diffuse light for use with highly reflective materials
- Expandable in 2" increments; Lengths from 2" to 24"
- Replaces the DL51120



### General Specifications

Electrical Specifications	Color	24v Current	All Other Controls
	625	0.2 A per 2"	0.2 A per 2" Max 24"
	470, WHI	0.2 A per 2"	0.2 A per 2" Max 24"
Normal Operating Temperature	0 - 60°C		
Weight (g)	Varies by size		
Standard Cable Information	Up to 2 meters (80") long - 105°C rated PVC jacket, foil shield with drain.		
Photobiological Risk Factor IEC 62471	Group 1 (Low-Risk) Applicable Wavelengths: 470, 625, WHI		
Compliance	  		
IP Rating	Not Rated		
Lumen Maintenance	L70 = 50,000 hours		

## Mechanical Specifications



Part #	Length in mm (inches)
DL15102	60.20 (2.37)
DL15104	111.00 (4.37)
DL15106	161.80 (6.37)
DL15108	212.60 (8.37)
DL15110	263.40 (10.37)
DL15112	314.20 (12.37)

DIMENSIONS ARE IN MILLIMETERS (INCHES)

2" increments up to a max of 24"

## Part Number Key

Model	Illuminated Length	—	Spectral Wavelength	Connector/Control	—	Alternative Connector
<b>DL151</b>	<b>XX</b>	<b>—</b>	<b>XXX</b>	<b>XX</b>	<b>—</b>	<b>XXX</b>
DL151	XX  2" Increments up to 24"		(blue) 470 (red) 625 (white) WHI	C1 C5 IC I3 I3S 24v		M12 <sup>1</sup>
Ex: DL15112-625C1 DL15106-WHII3			<sup>1</sup> Available with IC, I3, I3S and 24v options only			

**Stock Product:** *shipped next day*  
None


**Build to Order:** *shipped in two weeks*

## Connector | Control Options

C1 Connector	C5 Connector	IC	I3	I3S	24
For use with: DCS Series Controllers	For use with: Pulsar 320 Strobe Controller.	Continuous in-line controller  Powered with: 24V power supply	Combination strobe/continuous in-line controller  Powered with: 24V power supply	Default-OFF strobe/continuous in-line controller  Powered with: 24V power supply	Flying/tinned leads  Powered with: 24V power supply


## Optical Performance

### Intensity Distribution



Optical measurement taken using DL15112-WHIIC @ 25mm

### Area of Illuminance & Intensity



## Operation and Wiring

### ICS 2 (IC)

Pin (M12)	Function	Wire Color
1	+24 VDC	Brown
2	GHI	White
3	GND	Blue
4	GLO	Black
5	N/A	N/A


### ICS 3 (I3 and I3S)

Pin (M12)	Function	Wire Color
1	+24 VDC	Brown
2	Reserved	White
3	GND	Blue
4	PNP/Active High Trigger	Black
5	0-10 VDC Analog Control	Gray

### 24 Volt

Pin (M12)	Function	Wire Color
1	+24 VDC	Brown
2	N/A	White
3	GND	Blue
4	N/A	Black

### Optional M12 Pinout



## Warranty Information

Every Advanced illumination, Inc. (Ai) product is thoroughly inspected and tested before leaving the factory. Products are warranted to be free of defects in workmanship and materials for a period of two years from the original date of purchase. Should a defect develop during this period, please contact Ai Customer Service or your Ai distributor for a Return Merchandise Authorization (RMA), and return the complete product, freight prepaid, to Ai. If a defect is found, Ai will - at our discretion - repair or replace the product without charge. Ai claims no liability for any implied warranties, including "merchantability" and "fitness for a specific purpose."

## Electromagnetic Compatibility

This product was tested and complies with the regulatory requirements and limits for electromagnetic compatibility (EMC) as stated in the product specifications. These requirements and limits are designed to provide reasonable protection against harmful interference only when the product is operated in its intended industrial electromagnetic environment. To minimize the potential for electromagnetic interference or unacceptable performance degradation, install and use this product in strict accordance with the instructions in the product documentation.

## Customer Service

For information on existing orders, or to make an order adjustment, contact us Monday through Friday 8:00 am to 5:00 pm, EST or send an email to [orders@advill.com](mailto:orders@advill.com).

## Company Information

### **Advanced Illumination**

440 State Garage Road, Rochester VT. 05767

Phone: 802.767.3830

Fax: 802.767.3831

Email: [info@advancedillumination.com](mailto:info@advancedillumination.com)

Web: [advancedillumination.com](http://advancedillumination.com)

© 2015 Advanced Illumination Inc. All rights reserved