

Mega Speed X8 PRO



X8 PRO Back

4000 FPS MEGA Pixel High Speed Camera!

New Sensor Design!
Excellent Image quality!
So fast! So Easy!



Specifications

Work lights:	Built in high power LED work lights.	"Hot Swap" Solid State Drive Never Run Out Of Memory Again!
Temperature range:	0°C to 45°C Operational range. -40°C to +50°C storage range.	
Camera size:	Depth 7.8cm x width 22.8cm x height 12.5cm.	
Camera weight:	Mobile handheld camera. Light weight 1550g / 3.5 lbs with battery.	
Camera battery:	Lithium-ion re-chargeable / removable battery for minimum 5 hrs camera operation with power saving features.	
Input voltage:	14 VDC from wall adapter when required. Camera charges internal battery while plugged in and recording.	
Camera body:	Self contained, hand held with advanced light weight rugged shock absorbing Space Age ABS body.	
WiFi / LAN:	Camera can connect to LAN network and camera has optional WiFi connectivity.	
LCD screen:	Rear high resolution LCD screen. Full touch screen operation and control.	
Image Sensor:	1" color or monochrome 1280 x 800 format CMOS 10 bit, 14um pixel pitch.	
ISO Value	12,000.	
Low light setting:	25 fps, 40 ms exposure time for pre-capture setup and focus plus built in high power LED work lights.	
High Speed Mode:	4000 fps @ 1280 x 800 resolution and 100,000 fps at minimum resolution..	
Streaming Mode:	Camera can stream in long record mode to the internal SATA solid state drive	
Shutter speed:	Global electric shutter 2 us to 40 milli-seconds in precise 1-2 us steps for no high speed blur.	
Trigger in:	3 to 48 VDC TTL centre pin positive, manual, external or countdown timer.	
Data Acquisition:	Data acquisition connection of rear of camera to accept outside signal source.	
Input / output ports:	Triggers: Pre / Post, Single Sequence, Multiple Start/Stop & Continuous Mode Trigger, Sync. & ADC.	
Storage Options:	One hot swap SSD, 2 X USB & 2 X SD ports for use with USB flash drives and SD cards.	
File Formats:	User can save images in AVI, JPEG, BMP, TIFF, RAW and DNG file formats.	
Video Out Formats:	HDMI interface for TV / monitor and one optional 3GSDI out port.	
Optical interface:	Standard "C" Mount. "F" Mount is optional.	
Solid State Drive:	One hot swap re-moveable 640 GB Solid State Drive.	
Removable storage:	One solid state drive, 2 USB ports & 2 SD ports.	
Strobe/ Sync out:	3.3 VDC TTL via multi pin connector center pin positive, active high.	
Tripod Support:	Camera has integrated ¼ x 20 tri-pod thread.	
Camera RAM:	16 GB (Giga Byte) internal high speed internal image buffer memory.	
IRIG B:	Optional IRIG B time code ready via multi pin connector for IRIG B time stamping on recorded images.	
PC software:	Ships with Camera Control for image transfer, object tracking, image analysis, video editing software.	
PC requirements:	2GHz, 8 GB RAM. 1 USB and one Gig E connection. (Only needed if you connect camera to a PC)	
PC interface:	Gigabit Ethernet for full camera control and downloading files from the camera's solid state drive. User can also remove the SSD and connect it to the PC with the supplied USB DOC cable.	